Cornerstone Declaration of Performance

1. Unique Identification code: CLD30 Wintamix

2. Type, batch or serial number (or any other element) allowing identification of the product:

Production date and batch number is printed on the bag

3. Intended use: General Purpose Rendering/plastering Mortar (GP) (External)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer: Cornerstone, Brims Park, Old Callywith Road, Bodmin, Cornwall, PL31 2DZ

5. Authorised representative: Not Applicable

6. Assessment and Verification of Consistency of Performance: Level 4

7. In accordance with harmonized standard: EN998-1:2010

8. European Technical Assessment: Not Applicable

9. Declared Performance:

Reaction to Fire	Euroclass A1
Adhesion	0.20 N/mm2 – Fracture pattern B
Water Absorption (Declared)	W0
Water Vapour Permeability (Tabulated)	μ 15/35
Thermal Conductivity (Tabulated)	0.83 W/mK
Durability against Freeze/Thaw	Evaluation based on provisions valid in the intended place of use of the mortar

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in the table in point 9. This Declaration of Performance is issued under the sole responsibility of the manufacturer named in point 4 and is made in accordance with Annex ZA of EN998-2:2010.

Signed E. Walker

Name Mr Edward Walker

Position Technical Manager

Date 04/01/2016