

TRADIBLANC



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : TRADIBLANC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Binder for construction

1.3. Details of the supplier of the safety data sheet

Registered company name : CESA (Chaux et Enduits de Saint-Astier).

Address : 28 Bis route de Montanceix - La Jarthe.24110.Saint-Astier.France.

Telephone : +33(0)5.53.54.11.25. Fax : +33(0)5.53.04.67.91.

contact@saint-astier.com

www.saint-astier.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05



GHS07

Signal Word :

DANGER

Product identifiers :

EC 266-043-4

PORTLAND CEMENT CLINKER, CHEMICALS

EC 215-137-3

CALCIUM HYDROXIDE

Hazard statements :

H315

Causes skin irritation.

H318

Causes serious eye damage.

H335

May cause respiratory irritation.

Precautionary statements - General :

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P261

Avoid breathing dust

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

**TRADIBLANC**

## Precautionary statements - Response :

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/...
P332 + P313	If skin irritation occurs: Get medical advice/attention.

## Precautionary statements - Disposal :

P501	Dispose of contents/container in accordance with local regulations.
------	---

**2.3. Other hazards**

In use, may form flammable/explosive dust-air mixture.

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 65997_15_1 CAS: 65997-15-1 EC: 266-043-4  PORTLAND CEMENT CLINKER, CHEMICALS	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	[1]	25 $\leq$ x % < 50
INDEX: 471_34_1 CAS: 471-34-1 EC: 207-439-9  CALCIUM CARBONATE		[1]	25 $\leq$ x % < 50
INDEX: 1305_62_0 CAS: 1305-62-0 EC: 215-137-3 REACH: 01-2119475151-45-0242  CALCIUM HYDROXIDE	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	[1]	10 $\leq$ x % < 25
INDEX: 10101_41_4 CAS: 10101-41-4  SULPHATE DE CALCIUM DIHYDRATE		[1]	0 $\leq$ x % < 2.5

**Information on ingredients :**

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures****In the event of exposure by inhalation :**

In the event of massive inhalation of dust, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

---

**TRADIBLANC**

---

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.  
Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.  
If there is any redness, pain or visual impairment, consult an ophthalmologist.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.  
Watch out for any remaining product between skin and clothing, watches, shoes, etc.  
If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.  
In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.  
Seek medical attention immediately, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.  
Do not breathe in smoke.  
In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

No data available.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.  
Avoid inhaling dust.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Neutralise with an acidic decontaminant.  
Retrieve the product by mechanical means (sweeping/vacuuming) : do not generate dust.

**6.4. Reference to other sections**

No data available.

**TRADIBLANC**

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

**Fire prevention :**

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling dust.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture at all times.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Notes :
1305-62-0	1	-	4	-	-

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
471-34-1	-	10	-	-	-	-
1305-62-0	-	1	-	4	-	-
10101-41-4	-	10	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
65997-15-1	4 mg/m <sup>3</sup>				
471-34-1	10 mg/m <sup>3</sup>	-	-	-	TI
1305-62-0	1 mg/m <sup>3</sup>	4 mg/m <sup>3</sup>		Respirable fraction	
10101-41-4	4 mg/m <sup>3</sup>				

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

SULPHATE DE CALCIUM DIHYDRATE (CAS: 10101-41-4)

**TRADIBLANC**

---

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Inhalation.  
Long term local effects.  
10 mg of substance/m3

**CALCIUM HYDROXIDE (CAS: 1305-62-0)**

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Inhalation.  
Long term local effects.  
1 mg of substance/m3

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Short term local effects.  
4 mg of substance/m3

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Inhalation.  
Short term systemic effects.  
4 mg of substance/m3

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
1 mg of substance/m3

**CALCIUM CARBONATE (CAS: 471-34-1)**

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Inhalation.  
Long term local effects.  
4.26 mg of substance/m3

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
10 mg of substance/m3

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Inhalation.  
Long term local effects.  
1.06 mg of substance/m3

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
10 mg of substance/m3

**Predicted no effect concentration (PNEC):**

**CALCIUM HYDROXIDE (CAS: 1305-62-0)**

Environmental compartment:  
PNEC :

Soil.  
1.080

Environmental compartment:  
PNEC :

Fresh water.  
490

Environmental compartment:  
PNEC :

Sea water.  
0.32

**TRADIBLANC**

Environmental compartment: Fresh water sediment.  
PNEC : 3.004

CALCIUM CARBONATE (CAS: 471-34-1)  
Environmental compartment: Waste water treatment plant.  
PNEC : 100 mg/l

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

Prescription glasses are not considered as protection.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- PVC (polyvinyl chloride)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

These clothes shall be chosen to ensure there is no inflammation or irritation of the skin at the neck and wrist by contact with the powder

Suitable type of protective clothing :

Wear protective clothing against solid chemicals and particles suspended in the air (type 5) in accordance with standard EN13982-1/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid inhaling dust.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149/A1.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

**TRADIBLANC**

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Powder or dust.

**Important health, safety and environmental information**

pH : Not stated.  
Strongly basic.

Boiling point/boiling range : Not specified.

Flash point interval : Not relevant.

Vapour pressure (50°C) : Not relevant.

Density : > 1

Water solubility : Insoluble.

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

**9.2. Other information**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- formation of dusts

Dusts can form an explosive mixture with air.

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

---

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

**11.1.1. Substances**

**Acute toxicity :**

CALCIUM HYDROXIDE (CAS: 1305-62-0)

Oral route :

LD50 = 2000 mg/kg

Species : Rat

---

**TRADIBLANC**

---

	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Dermal route :	LD50 = 2500 mg/kg Species : Rabbit OECD Guideline 402 (Acute Dermal Toxicity)
CALCIUM CARBONATE (CAS: 471-34-1)	
Oral route :	LD50 > 2000 mg/kg Species : Rat OECD Guideline 420 (Acute Oral Toxicity Fixed Dose Method)
Dermal route :	LD50 > 2000 mg/kg Species : Rat OECD Guideline 402 (Acute Dermal Toxicity)
Inhalation route (Dusts/mist) :	LC50 > 3 mg/l Species : Rat OECD Guideline 403 (Acute Inhalation Toxicity)
<b>Skin corrosion/skin irritation :</b>	
CALCIUM HYDROXIDE (CAS: 1305-62-0)	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
CALCIUM CARBONATE (CAS: 471-34-1)	Species : Rabbit OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
	Species : Rabbit OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
<b>Serious damage to eyes/eye irritation :</b>	
CALCIUM CARBONATE (CAS: 471-34-1)	Species : Rabbit OECD Guideline 405 (Acute Eye Irritation / Corrosion)
	Species : Rabbit OECD Guideline 405 (Acute Eye Irritation / Corrosion)
	Species : Rabbit OECD Guideline 405 (Acute Eye Irritation / Corrosion)
	Species : Rabbit OECD Guideline 405 (Acute Eye Irritation / Corrosion)
<b>Respiratory or skin sensitisation :</b>	
CALCIUM CARBONATE (CAS: 471-34-1)	
Local lymph node stimulation test :	Non-Sensitiser. Species : Mouse OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Guinea Pig Maximisation Test (GMPT) :	Non-sensitiser. Species : Mouse OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Buehler Test :	Non-sensitiser.



**TRADIBLANC**

---

Species : Mouse  
OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity :**

CALCIUM CARBONATE (CAS: 471-34-1)

No mutagenic effect.

Mutagenesis (in vitro) :

Negative.  
OECD Guideline 471 (Bacterial Reverse Mutation Assay)

**Carcinogenicity :**

CALCIUM CARBONATE (CAS: 471-34-1)

Carcinogenicity Test :

Negative.  
No carcinogenic effect.  
Species : Human

**Reproductive toxicant :**

CALCIUM CARBONATE (CAS: 471-34-1)

No toxic effect for reproduction

Study on development :

Species : Rat  
OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the  
Reproduction / Developmental Toxicity Screening Test)

**Specific target organ systemic toxicity - repeated exposure :**

CALCIUM HYDROXIDE (CAS: 1305-62-0)

Oral route :

C = 36 mg/kg bodyweight/day  
Duration of exposure : 90 days

CALCIUM CARBONATE (CAS: 471-34-1)

Oral route :

C = 1000 mg/kg bodyweight/day  
Species : Rat  
Duration of exposure : 90 days  
OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the  
Reproduction / Developmental Toxicity Screening Test)

Inhalation route :

C = 0.212 mg/litre/6h/day  
Species : Rat  
Duration of exposure : 90 days  
OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

**11.1.2. Mixture**

No toxicological data available for the mixture.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

CALCIUM HYDROXIDE (CAS: 1305-62-0)

Fish toxicity :

LC50 = 50.6 mg/l  
Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 49.1 mg/l  
Duration of exposure : 48 h

Aquatic plant toxicity :

ECr50 = 184.57 mg/l

**TRADIBLANC**

---

Duration of exposure : 72 h

CALCIUM CARBONATE (CAS: 471-34-1)

Fish toxicity :

Species : *Oncorhynchus mykiss*

Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

Species : *Daphnia magna*

Duration of exposure : 48 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity :

ECr50 > 14 mg/l

Species : *Desmodesmus subspicatus*

Duration of exposure : 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

#### 12.2.1. Substances

CALCIUM HYDROXIDE (CAS: 1305-62-0)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

PORTLAND CEMENT CLINKER, CHEMICALS (CAS: 65997-15-1)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

### 12.3. Bioaccumulative potential

No data available.

#### 12.3.1. Substances

CALCIUM CARBONATE (CAS: 471-34-1)

Octanol/water partition coefficient :

log K<sub>ow</sub> < 3.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

No data available.

---

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**TRADIBLANC**

---

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/1182 (ATP 15)

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

**TRADIBLANC**

---

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.