



Fine Surface Filler Datasheet

Fine surface filler can be used to fill cracks and hide blemishes in renders, it is a porous, vapour open material suitable for use with lime renders and plasters.

Application

Prepare the surface you want to use the filler on, remove any dust or dirt from the surface and brush out any loose material from the edges of a crack. Thoroughly wet out the area you will be applying the filler.

Mix the required quantity of Fine Surface filler with water to give you a paste like consistency – It sets after roughly an hour depending on the temperature, so do not mix more than you require.

After application keep the area damp for a day or so to allow the filler to gain strength. After it has gained enough strength it should be sand-able for the next couple of days, however we cannot tell you exactly when this will be as it will depend on how absorbant the background is it has been applied to.

We recommend painting with a vapour open paint afterwards to hide any mismatch or scarring where the filler was used.

Health and Safety

Wear all appropriate PPE for handling Lime Mortars. This includes but is not limited to; Long sleeve clothing, goggles and gloves. For full details please obtain a MSDS.

Storage and Shelf Life

The Fine Surface Filler should be kept in cool dry conditions. It has a shelf life of approximately 9 months from the date of manufacture. If you only use part of a tub it should retain that shelf life so long as the tub is properly resealed after use.

Disposal

Any unused filler should be mixed with water and allowed to harden, this can then be disposed of in normal waste bins. Rinse the tub out well with water and recycle.